Item Code	Qty	Description	Mark No.
C0-00DD2-D	1	CLICK Basic PLC, 24 VDC required, serial ports, Discrete Input: 8-point, DC, Discrete Output: 6-point, sourcing.	1
FAZ-B16-1-NA-L-SP	1	Eaton miniature circuit breaker, current-limiting, 16A, 240 VAC / 48 VDC, 1-pole, B curve, thermal magnetic, 14kA SCCR, 35mm DIN rail mount.	2
ZP-S1-3MR-0P3M	1	ZIPport bulkhead connector, 7/8in - 16 UN2 thread barrel 3-pin male to pigtail, 16 AWG, 0.9ft/0.3m cable length, PVC conductor insulation material, North American color code. Mounting nut(s) included.	3
7231-13541-9710050	1	Bulkhead connector, M12 nut 4-pin female to pigtail, 22 AWG, 1.6ft/0.5m cable length, polypropylene conductor insulation material. Mounting nut(s) included.	4
783-3C-24D	1	Ice cube control relay, socket mount, encapsulated push-to-test, 24 VDC coil voltage, 3PDT, 15A contact rating, 11-pin, LED indicator(s). Purchase 783-3C-SKT mounting socket separately.	5
783-3C-SKT	1	Relay socket, 35mm DIN rail or panel mount. For use with 783 series cube relays.	6
KN-TL14	1	Konnect-It screw triple-level feedthrough terminal block, accepts wire size 24-12 AWG, gray, 24A, 300V rated (UL), 35mm DIN rail mount, 100kA SCCR. Package of 20. For use with jumpers KN-2JTL12, KN-3JTL12, KN-4JTL12 and KN-10JTL12.	7
T1E-1015G-1	1	Iboco T1E series open slot thin finger wire duct, 1in width, 1.5in height, 6.5ft/2m length, gray. Cover included.	8
N1C121408	1	Hubbell-Wiegmann enclosure, NEMA 1, 14 x 12 x 8in (HxWxD), wall mount, carbon steel, ANSI 61 gray, light-textured polyester powder finish, single-door, 1/4-turn flush-mounted latch.	9
N1P1214	1	Hubbell-Wiegmann subpanel, carbon steel, white, polyester powder coat finish. For use with 14x12 (HxW) N1C12140x and WA141206GIE enclosures.	10
EA3-S3ML-R	1	C-more Micro EA3 series touch screen HMI, 3in monochrome STN LCD, 128 x 64 pixel, LED backlight, supports (1) serial port.	11
BNBCX-02	1	Bimed cable gland, 1/2in NPT thread type, nickel-plated brass, accepts 6 to 12mm diameter cable, IP68. Package of 5. Mounting hardware included.	12
BRY5266NP	1	Straight blade plug, 15A, 125 VAC, 2-pole, 3-wire, NEMA configuration 5-15, nylon housing, black and white.	not shown
SOOW-14-3BK-1 Length : 20	1	Southwire flexible portable cord, Type SOOW, 600V, 3 conductors (includes ground), 14 AWG, EPDM thermoset rubber conductor insulation material, black, white and green, CPE thermoset rubber jacket, black, cut to length.	not shown
KN-10JTL12	1	Konnect-It terminal block jumper, screw-down type, 10-pole, 24A, 440V. Package of 5. For use with multiple terminal blocks.	13
KN-ECTL	1	Konnect-It terminal block end cover, gray. Package of 10. For use with KN-TL14 series terminal blocks.	14
GCX3350	1	Selector switch, 22mm, 2-position, maintained, (1) N.O. contact(s), plastic base, plastic bezel, Operator: black, lever, 30mm, round, plastic.	15
PSB24-060-P	1	Power Supply, 24 vdc, 60W, 2.5A	16

DRAWING NO.	AA1008GA	REV 1
SIZE: B	SCALE 1 = 1	SHEET 2